

# BeyondVoice™

## Phone System Interface Options

	Analog	Digital – T-1 CAS	Digital – PRI
<b>Number of Lines Supported</b>	5 – 14 lines BeyondVoice™ I	9 – 14 lines BeyondVoice™ I	9 – 14 lines BeyondVoice™ I
	15 – 24 lines BeyondVoice™ II	15 – 24 lines BeyondVoice™ II	15 – 23 lines BeyondVoice™ II
<b>Caller ID Options/ Availability</b>	Name & Number	None	Number Only
<b>Account Code Availability</b>	Yes	Yes	No
<b>Availability of Other Features</b>	Yes	No, phone system provides features	No, phone system provides features
<b>DID (Direct Inward Dial)</b>	No	Yes	Yes
<b>Hunt Group/ Trunk Group Options</b>	Hunting Provided	Standard: One Combo trunk	Only 1 Combo trunk group
<b>Phone Number Level Billing</b>	Yes	No	No
<b>Installation Interval</b>	30-45 Days  (60 days if more than 17 phone lines)	30-45 Days	60 Days
<b>Outbound Caller ID Display</b>	One Number/ Line	One Number/ Trunk Group	Depends on PBX configuration*

\*PBX must be set to send 10 digits.

**CAS** = Channel Associated Signaling      **PRI** = Primary Rate Interface

